




Specification for In-Ground Waste and Recycling Containers – EarthBin Premium




Front view



Side view



Front elevation



Top view



Model:	EB500
Capacity/Volume:	6.5 cu. yd. (5000 litres)
Capacity/Weight:	2600 lbs (1200 kg)
Width (A):	80 in. (203 cm)
Length (B):	70 in. (178 cm)
Height (C):	55 in. (140 cm)
Feed Height (D):	45 in. (114 cm)
Depth In-Ground (E):	62 in. (158 cm)
Ground sleeve height above finished grade. (F):	4 in. (10 cm)
Waste Feed Opening:	19 x 24 in. (48 x 61 cm)
Cardboard Feed Opening:	6 x 24 in. (15 x 61 cm)
Weight (Empty):	750 lbs (340 kg)
Configuration:	<ul style="list-style-type: none"> • Rectangular container above-ground; • Round container in-ground which can be rotated
Feed Doors:	<ul style="list-style-type: none"> • Two (2) per container (front & rear) • Colour coded to indicate purpose (green, blue, grey, or black) • Lockable feed doors
Locks:	<ul style="list-style-type: none"> • Two (2) automatic Gravity Latches on main Service Lid
Materials:	<ul style="list-style-type: none"> • Rigid roto-molded premium virgin polyethylene ground sleeve • Rigid roto-molded premium virgin polyethylene bin • Polyethylene vacuum formed (thermoformed) Service Door & Feed Doors with textured surface finish • Yellow zinc plated steel frame with a Super durable sandtex powder paint • Fastened aluminum anodized signage • Polyethylene vacuum formed architectural panels
Other:	<ul style="list-style-type: none"> • Lifting structure conforms to standard Front Load waste trucks • Manual Lid Strut on both feed doors • Durable & fade resistant; non-warping lids and feed doors • Secondary Containment In-Ground System • Cardboard slot is covered and lockable • Patented ground sleeve anchor system • Protective black bumpers • Bin is comprised of two (2) parts • Architectural panels available in optional colours

*SPECIFICATIONS MAY CHANGE WITHOUT NOTICE